









## T.V.R. VIXEN 1600 S.2. SPECIFICATION:

stroke 77.6mm developing 92bhp at 5500 rpm, compression ratio 9.0 to 1, overhead valves, single compound twin choke carburettor with circulation thermostatically heat controlled water air silencer, mechanical fuel pump ENGINE: Four cylinder 1599 c.c. bore 80.97mm.

quarter mile 17 secs. Top speed 114 mph approx secs, 0-70 mph 12.8 secs. approx. Standing PERFORMANCE: 0-30 mph 3.4 secs, 0-50 mph 7.1

syncromesh gearbox providing ratios of 3.89, 5.450, 7.839 and 11.50 to 1 and reverse 12.963 to GEARBOX: Four forward speeds in all

3.89 to 1 ratio 18.8 mph per 1000 revs. hypoid level spline drive shaft to wheels. FINAL DRIVE: Chassis mounted differential

by wishbones and telescopic coil spring/damper units. Anti roll bar to front. SUSPENSION: Independent suspension all round

employing self-adjusting disc brakes at front and drum brakes at rear. Front disc. dia. 10", rear drum  $9" \times 13"$ . Emergency warning device BRAKES: Servo assisted dual braking systems warning light on each separate system also hand brake

from steel tubing with outriggers CHASSIS: Multi-tubular backbone constructed

5½ x 15 wheels. tyres. Optional aluminium alloy Super Sport WHEELS: Disc type with 4½" rims 165 x 15 SR

Seat adjustment Headroom from seat cushion Turning circle Ground clearance Track front Wheelbase Overall height Overall width Overall length DIMENSIONS rack rear

54 53 90 48 s ins ins # ins ins ins ins ins ins ins 3683 mm. 1219 2296 8.23 1371 1346 863 127 mm mm mm. mm mm mm mm. mm.

> BODY:Two doors, closed G.T. body in high finish reinforced polyester, finished in winding windows. cellulose paint. Forward hinged doors,

brake lamps and reflectors in wraparound form Number plate lamp and reversing lamp. focus headlamps, separate parking lamps and direction indicator flashers. Rear lamps, LIGHTS: Flush fitting sealed beam with pre-

headlamp beam, ignition direction indicators temperature gauge, oil pressure gauge, fue INSTRUMENTS: Speedometer, tachometer and reverse gauge and ammeter. Warning lights for main

steering wheel boss. Electric screen washers Self-cancelling direction indicator control by steering column lever. Horn button on column switch with daylight flasher switch hand. Headlamp beam selection by steering switch and screen wiper switch by drivers pull, lights, heater, panel and reverse light wheel, (rack and pinion), Ignition lock, choke CONTROLS: Three spoke wood rim steering

competition type seats. UPHOLSTERY: Ambla, separate adjustable

section behind seats. Lidded glove compartment LUGGAGE ACCOMMODATION: On flat floor

approx. Fuel consumption 26-30 mpg. FUEL TANK CAPACITY: 15 Imp. gallons, 68 litres

wheels, leather steering wheel, seat belts, non standard colour, radio, suppression kit and aerial, Dunlop SP sport tyres, Michelin XAS tyres, laminated windscreen, laminated tract. tinted windscreen, tinted side windows OPTIONAL EXTRAS: Aluminium alloy 52" x

BISPHAM ROAD, BLACKPOOL FIELDINGS INDUSTRIAL ESTATE, TEL. 0253-33241/2 TVR ENGINEERING LIMITED

