



**THE 1974  
TVR 3000 'M'  
SERIES**



## NEWS BULLETIN

### TVR 3000M SPECIFICATION

#### ENGINE:

Cylinders	Vee 6
Bore	93.97 mm.
Stroke	72.41 mm.
Cubic Capacity	2994 cc.
Compression Ratio	8.9 : 1
Fuel Pump	AC Mechanical
Oil Filter	AC Full Flow
Carburettor	Dual Choke Weber
Max. Power	142 bhp Nett at 5000 rpm.
Max. Torque	172 lb. ft. at 3000 rpm.

#### TRANSMISSION:

Clutch	242 mm. dia.
Top Gear Ratio	1.00 : 1
3rd Gear Ratio	1.41 : 1
2nd Gear Ratio	1.95 : 1
1st Gear Ratio	3.16 : 1
Rev. Gear Ratio	3.35 : 1
Final Drive	3.45 : 1

#### M. P. H. AT 1000 REVS.

Top Gear	21.6
3rd Gear	15.32
2nd Gear	11.08
1st Gear	6.84

#### SPEED IN GEARS AT 6000 rpm.

*4th	130 mph
3rd	91 mph
2nd	66 mph
1st	41 mph

\* Depending on conditions

PERFORMANCE Approx.

0-60 mph	7.5 sec.
Maximum Speed	125+ mph
Fuel Consumption	22 mpg Nominal

BRAKES

Disc Front	10.875 in. dia.
Drum Rear	9 in. dia. x 1 $\frac{3}{4}$ "
Dual Circuit	Servo-Assisted

SUSPENSION

Front Independant & Double WISHBONES	Coil Springs
Rear Independant & Double WISHBONES	Coil Springs

STEERING

Rack and Pinion

SHOCK ABSORBERS

Front	Telescopic
Rear	Telescopic

WHEELS AND TYRES

6JK x 14 in. dia. TVR Aluminium Alloy

185 x 14 HR Radial Ply Tyres

BATTERY

12 Volt Negative Earth. 58 Ah.

DIMENSIONS

Wheelbase	7'6"
Track Front	4'5 $\frac{3}{4}$ "
Rear	4'5 $\frac{3}{4}$ "
Overall Length	13'8"
Width	5'4"
Height	3'11"
Ground Clearance	5"
Turning Circle Right	35'9"
Turning Circle Left	35'9"
Fuel Tank Capacity	12 gallons

TVR Engineering Limited reserves the right to vary specifications of all products manufactured by them at any time.

For further press facilities and information contact:

Michael Casale,  
M.A.P. (Public Relations),  
243 Caledonian Road,  
LONDON N1 1ED.

Tel: 01-837-9852/3 (24 hour Ansafone).